



QP - WR354N

Router AP Inalámbrico para interiores

Router AP Inalámbrico para interiores 300Mbps

Características

- Modo inalámbrico: AP, Cliente, WDS, AP+WDS
- Firewall, URL/IP/Port/Filtro MAC
- Soporta PPPoE, VPN pass-through(PPTP y L2TP)
- WPS (Wi-Fi Configuración Protegida) vía PIN
- Fácil asistente de configuración con utilidad basada en Web
- Soporta tecnología avanzada 2 x 2 MIMO con hasta 300Mbps de descarga y carga de datos

Especificaciones

Standard

- IEEE 802.11b/g/n

Antenna

- Two detachable 2dBi antennas

Chipset

- Realtek RTL8196C

Frequency Band

- 2.400GHz ~ 2.484GHz

Data Rate

- 802.11b: 11,5.5,2 and 1 Mbps with auto-rate fall back
- 802.11g: 54,48,36,24,18,12,9&6Mbps
- 802.11n: (20MHz) up to 144Mbps
- 802.11n: (40MHz) up to 300Mbps

Operation Mode

- Gateway
- Bridge
- Wireless ISP

Wireless Mode

- AP
- Client
- WDS
- AP+WDS

Security

- 64/128 bit WEP
- WPA (TKIP with IEEE 802.1x)
- WPA2(AES with IEEE 802.1x)

- WPA Mixed

Media Access Control

- CSMA/CA

Power requirement

- 12V DC

Operation Temperature

- 0°C ~ 60°C ambient temperatura

Storage Humidity

- 10% ~ 90% (Non-condensing)

Sensitivity

- 93dBm @ 802.11b
- 88dBm @ 802.11g
- 87dBm @ 802.11n

Output Power (Typical)

- 802.11b: up to 19 ± 1 dBm
- 802.11g: up to 16 ± 1 dBm
- 802.11n: up to 15 ± 1 dBm

Dimension(mm)

- 149(L) x104(W) x25(H)

Connector

- Two antennas connector
- One RJ-45 WAN port
- Four RJ-45 LAN port
- Reset to default button
- Power jack
- WPS button

